



DetectaTape[®]

Farington Mill, Centurion Industrial Estate,
Centurion Way, Leyland, PR25 4GU

T: 01772 434444 E: sales@customtape.co.uk

Product Spec Sheet

Detectable Underground Warning Tape

LDPE tape, with twin 0.5mm stainless steel tracer wires.
Coloured tape with black print, overlaminated with hotmelt polypropylene.

Physical Properties

Material:	Low Density Polythene (LDPE)
Country of Origin:	United Kingdom
Description:	Single Wound Sheet (SWS) Treated for 1 print side
Tensile Strength:	15MN/m ²
Slip Level:	Low
Shrink:	N/A
Base Colour:	As required (BS range)
Ink:	Highly resistant, solvent based
Print Colour:	Black
Text:	As required
Packaging:	Supplied as rolls on 75mm (internal ID) cardboard cores

Roll Dimensions

Roll Size:	150mm x 100m
Roll Thickness:	100 micron (0.1mm average) (please note the average thickness shall be 0.1mm (+/- 0.015mm))
Core:	76mm diameter cardboard core
Elongation:	>400%
Reel Length:	250mtrs - 1000mtrs
Tolerance:	As per our current house standards +/- 10%

**THE ABOVE SPECIFICATION IS MANDATORY AND CAN ONLY BE ALTERED
WITH THE WRITTEN AGREEMENT OF THE SUPPLIER**

Complies with ENA TS 12-23 Issue 3 2013

BS EN 12613: 2009

Date: 04/01/2019